900 Control Station

Protective film

| Order Part No. | Qty. | <u>Description</u> |
|----------------|------|---|
| 50038816-501 | 10 | 0.003" thick clear polyester sheet for 900CS10-00 |
| | | (10 inch display) |
| 50038816-502 | 10 | 0.003" thick clear polyester sheet for 900CS15-00 |
| | | (15 inch display) |

Document Number Form: 51-52-33-159

Effective Date: October 2009

Summary

The films are a convenient way to protect the front of the 900 Control Station in dirty or abrasive environments such as foundries and concrete plants. The low-tack adhesive allows them to be applied directly to the display. Their large size provides protection for the keys as well as the screen.

Tools required

Thin non-metallic object (for removing old film)

Procedure

Table 1 Installation

| Step | Action |
|------|---|
| 1 | Clean the front surface of the 900 Control Station. Note: It is suggested you first access Main Menu>Station Settings>Station Setup>Clean Screen. This will allow you to touch the screen without effect. |
| 2 | Peel away the backing from one edge of the film. |
| 3 | Align and attach that edge to the corresponding edge of the unit. |
| 4 | Slowly remove the remaining backing from the film as you slowly apply the film to the front. Use a wiping action to minimize air pockets. Press entire area to achieve best adhesion. |

Table 2 Removal

| Step | Action |
|------|---|
| 1 | Start by lifting a corner of the film with a non-metallic object. |
| 2 | To remove, slowly pull one corner towards the other corners. |