



SLP Series

Cost effective surge protection for digital and analogue I/O

- Surge protection for two loops per SLP (or one 4-wire circuit)
- Range of ATEX Certified intrinsically safe surge protectors
- Multi-stage hybrid protection circuit — 20kA maximum surge current
- Range of voltage ratings — to suit all process I/O applications
- Designed for high bandwidth, low resistance applications
- 10 year product warranty



The SLP Series is a range of surge protection devices combining high packing densities, application versatility, proven hybrid circuitry and simple installation – features which make the series the most cost effective surge protection solution for process control equipment systems and communications networks.

The multi-stage hybrid surge protection network at the heart of the SLP uses a combination of solid state electronics and a gas filled discharge tube (GDT) to provide surge protection up to 20kA. This impressive surge protection circuit is designed to exhibit exceptionally low line resistance and adds only a tiny voltage drop to the circuit.

In operation, the SLP device does not adversely affect the performance or operation of the loop or combined equipment. The device allows signals to pass with very little attenuation while diverting surge currents safely to earth and clamping output voltages to safe levels.

Fully automatic in operation, SLP devices react immediately to make sure that equipment is never exposed to damaging surges between lines or the lines and earth. Reacting instantaneously, the SLP redirects surges safely to earth and then resets automatically.

The versatile SLP series design considers the need for high packing densities and has a product combining protection for two process loops into one case. Each module provides full hybrid surge protection for two process loops.

For higher bandwidth applications, the SLP series has been developed to meet the demands of today's highest speed communication systems.

One simple manual operation clamps modules securely onto DIN rail, which automatically provides the essential high-integrity earth connection.

A 10 Year 'No Fuss' warranty is available as standard for the SLP so if a correctly connected device should fail for any reason, simply return it for a free replacement.

'Top-hat' (T-section) DIN rail is generally suitable for mounting SLP modules although for adverse environments, a specially-plated version is available.

SPECIFICATION

All figures typical at 77°F (25°C) unless otherwise stated

Maximum surge current

20kA (8/20µs waveform) per line

Leakage current

<1µA @ working voltage

Maximum rated load current

1.50A

Loop resistance

2 ohm

Capacitance

Line to Line: 60pF

Attenuation

-0.1db @ 9kHz - 37MHz

-3dB @ 50MHz

Response time

<1ns

Ambient temperature

-40°F — +158°F

(-40°C — +70°C) — working

-40°F — +176°F

(-40°C — +80°C) — storage

Humidity

5 to 95% RH (non-condensing)

Terminals

2.5mm² (12 AWG)

Electrical connections

Plug/header screw terminal strip

Mounting

T-section DIN-rail (35 x 15mm rail)

Weight

5oz (140g approximately)

Case flammability

UL94-V0

EMC compliance

BS EN 60950:1992

BS EN 61000-6-2:1999

BS EN 61010-1:1993

BS EN 61000-4-5:2006

Electrical safety

See approvals below right

Model		SLP07D	SLP16D	SLP32D
Nominal voltage	U_n	7V	16V	24V
Rated voltage (MCOV)	U_c	8V	18V	32V
Nominal current	I_n	1.50A	1.50A	1.50A
Nominal discharge current (8/20µs)	i_{sn}	3kA	3kA	3kA
Max discharge current (8/20µs)	I_{max}	20kA	20kA	20kA
Lightning impulse current (10/350µs)	I_{imp}	2.5kA	2.5kA	2.5kA
Residual voltage @ i_{sn}	U_p	10V	23V	40V
Voltage protection level @ 1kV/µs	U_p	<8V	<18V	<38V
Bandwidth	f_G	50MHz	50MHz	50MHz
Capacitance	C	60pF	60pF	60pF
Series resistance	R	1.0	1.0	1.0
Operating Temperature Range		40°C to +80°C		
Category tested		A2, B2, C1, C2, C3, D1		
Overstressed fault mode $i_{n1}=3kA$		22kA	22kA	22kA
Impulse durability (8/20µs)		10kA	10kA	10kA
Degree of protection		IP20		
AC durability		1A _{rms} , 5T		
Service conditions		80kPa - 160kPa 5% - 95% RH		

Tested in accordance with IEC 61643-21.

SIL INFORMATION

Failure rates according to IEC 61508

	λ_{SD}	λ_{SU}^*	λ_{DD}	λ_{DU}
SLP07D	0	128	41	2
SLP16D	0	128	41	2
SLP32D	0	128	41	2

The user of the SLP Series can utilize these failure rates in a probabilistic model of a safety instrumented function (SIF) to determine the suitability in part for safety instrumented system (SIS) usage in a particular safety integrity level.

*The Residual Effect failures are included in the Safe Undetected failure category according to IEC 61508. Note that these failures alone will not affect system reliability or safety and should therefore not be included in spurious trip calculations.

Safe Failure Fraction needs to be calculated on (sub)system level.




Figure 1 Dimensions




Figure 2 Connection details

APPROVALS

Country (Authority)	Standard	Certificate/ File No.	Approved for	Product
Europe (Baseefa)	EN 50014:1997 + A1 & A2 EN 50020:2002 EN 60079-26:2004	Baseefa04ATEX0303X	EEx ia IIC T4	SLP07D, SLP16D, SLP32D
Europe (MTL)	BS EN 50014:1998 BS EN 50021:1999 EN 60079-15:2003	MTL03ATEX0377X	EEx n IIC T4	SLP07D, SLP16D, SLP32D
USA (FM)	Class Nos. 3600 (1998), 3610 (2010), 3611 (1999), 3615 (1989), 3810 incl. Supp 1 (1995-07 (1989-03), ANSI/NEMA 250 (1991) ANSI/ISA 60079-0 (2009) ANSI/ISA 60079-11 (2009) ISA-S12.0.01 (1999)	3011208	IS/1/A-D I/O/AEx ia IIC I/O/AEx ia IIB NI/1/2/A-D NI/1/2/IIC	SLP07D, SLP16D, SLP32D
Canada (FM)	C22.2 No. 213, 142, 94, 157, 30 ANSI/NEMA 250 CAN/CSA-E79-0 CAN/CSA-E79-11	3025374C	IS/1/A-D I/O/AEx ia IIC I/O/AEx ia IIB NI/1/2/A-D NI/1/2/IIC	SLP07D, SLP16D, SLP32D

The given data is only intended as a product description and should not be regarded as a legal warranty of properties or guarantee. In the interest of further technical developments, we reserve the right to make design changes.



EUROPE (EMEA): +44 (0)1582 723633
enquiry@mtl-inst.com

THE AMERICAS: +1 800 835 7075
csinfo@mtl-inst.com

ASIA-PACIFIC: +65 6 645 9888
sales.mtl@cooperindustries.com

901-106 Rev L 111010